



PVCu Frame Cleaner Solvent B.

Product description

PVCu Frame Cleaner Solvent B. is a highly effective, fast acting, non-smear, liquid cleaning agent suitable for removing ingrained dirt and marks on white PVCu frames and other plastics.

Properties

- Fast acting
- Fast drying
- Ready to use
- Non-smearing
- Restores to a clear and shiny finish
- Perfumed
- Multi-purpose use
- Non-abrasive
- Highly flammable



Applications

- Cleaning of most types of PVCu frames, sills, cladding, panels and trims.
- For removing most ingrained dirt, grease, uncured sealant, pencil and pen mark.
- Cleaning of plastic garden furniture.

Technical data

Base	Solvent mixture
Consistency	Fluid
Density	ca. 0.90 g/ml
Application temperature	+5°C → +25°C

Footnote: Skinning time and curing speed may vary depending on environmental factors such as temperature, moisture, and type of substrates.

Substrates

- Substrate condition
Dirty
- Substrate preparation
No pretreatment required.
- Suitable substrates
white PVCu window frames hard PVC,

Application method

- Application method
For best results, apply and spread PVCu Frame Cleaner Solvent B. onto surface with a clean, soft, colourfast cloth or paper tissue, working well into the surface. Leave to rest for a few minutes. Wipe away contamination and then polish the cleaned surface using a second dry cloth or paper tissue. Always work with a clean cloth to avoid contamination of the surface. Always wipe in one direction.

PVCu Frame Cleaner Solvent B.

Health- and Safety Recommendations

Take the usual labour hygiene into account. Consult the packaging label and safety data sheet for more information.

Use only in well-ventilated areas.

Always wear gloves and goggles.

After contact with skin rinse immediately with soap and water.

Ingestion : rinse off the mouth with running water avoiding ingesting the liquid.

Get in touch with a doctor.

The user has to check if the product is suitable for the specific application.

Packaging/Logistics

Colour: Colourless

Packaging: 1 L bottle

Shelf life: 12 months in unopened packaging in a cool and dry storage place at temperatures between +5°C and +25°C

Remarks

- It is recommended to do a compatibility test prior to application.
- Not recommended with veneered, foiled or painted PVCu.
- PVCu Frame Cleaner Solvent B. should not be diluted.

This technical data sheet replaces all previous versions. The directives contained in this documentation are the result of our experiments and of our experience and have been submitted in good faith. It is general in nature and does not constitute any liability. Because of the diversity of the materials and substrates and the great number of possible applications which are out of our control, we cannot accept any responsibility for the results obtained. Since the design, the quality of the substrate and processing conditions are beyond our control, no liability under this publication is accepted. It is the responsibility of the user to determine by his own tests whether the product is suitable for the application. In every case it is recommended to carry out preliminary experiments. The manufacturer reserves the right to modify products without prior notice.