

ACRYRUB PRO+

Revision: 01/04/2024

Page 1 of 2

Technical Data

Basis	Acrylic Dispersion
Consistency	Paste
Curing System	Physical drying
Specific Gravity	1.67±0.05
Skin formation time (20°C/65% R.H.) (min)*	Approx. 20
Shrinkage (%)	Approx. 15
Maximum allowed Distortion (%)	15
Temperature Resistance (°C)	-20 to +80
Application Temperature (°C)	-5 to +30

*These values may vary according to ambient conditions such as temperature, humidity, substrate etc.

Description:

Acryrub PRO+ is a high-quality, plasto-elastic one-component joint sealant based on acrylic dispersions.

Properties:

- Very easy to apply
- Colourfast and waterproof after curing
- Can be painted over after curing
- Very good adhesion on many porous surfaces, aluminium and uPVC.

Applications:

- Joints with movements up to 15%
- Connection joints in the building industry
- Joints between windowsills, between skirting board and floor, between brickwork, etc

Packaging:

Colour: White, Brown, Grey, Black
Packaging: 450g

Shelf life and storage:

12 months from date of manufacturing in unopened packaging stored in a cool and dry place at recommended temperatures between +5°C and +25°C. Protect against frost!

Health and safety recommendation:

Apply the usual industrial hygiene.
Consult the label for more information.

Joint Dimensions:

Minimum Width: 5mm
Maximum Width: 20mm
Minimum Depth: 5mm
Recommendation: joint depth = joint width

Use PE backer rods in case of large joint dimensions to avoid three - sided adhesion

Substrates:

Type: all porous building surfaces
State of Surface: clean, dry, free of dust and grease
Preparation: prepare very porous surfaces with diluted Acryrub Pro+ (1 part Acryrub Pro+ & 2 parts water)

We recommend a preliminary compatibility test.

Application Method:

Method: Apply the sealant by means of a hand held or pneumatic caulking gun. Smoothen the sealant with a filling knife.

Remark: The directives contained in this documentation are the result of our experiments and of our experience and have been submitted in good faith. Because of the diversity of the materials and substrates and the great number of possible applications which are out of our control, we cannot accept any responsibility for the results obtained. In every case it is recommended to carry out preliminary experiments.

Soudal India Pvt. Ltd.

Plot No. 200, Sec. 4, Phase - II, Growth Centre, Bawal, Dist. Rewari, Haryana - 123501 (India)
info@soudal.in | www.soudal.in | +91 8010-114-114

ACRYRUB PRO+

Revision: 01/04/2024

Page 2 of 2

Application temperature: +5°C to +30°C, do not apply when rain or frost are imminent.

Clean: Uncured Acryrub Pro+ can be removed from tools with water. Cured sealant must be removed mechanically.

Finishing: with water

Remarks:

- Do not use in applications where continuous water immersion is possible.
- Do not apply when rain or frost is imminent.
- The paint should be sufficiently elastic to be applied on a plasto-elastic sealant. A preliminary test is recommended.
- Acryrub Pro+ can be painted over with most paints.

Remark: The directives contained in this documentation are the result of our experiments and of our experience and have been submitted in good faith. Because of the diversity of the materials and substrates and the great number of possible applications which are out of our control, we cannot accept any responsibility for the results obtained. In every case it is recommended to carry out preliminary experiments.

Soudal India Pvt. Ltd.

Plot No. 200, Sec. 4, Phase - II, Growth Centre, Bawal, Dist. Rewari, Haryana - 123501 (India)
info@soudal.in | www.soudal.in | +91 8010-114-114