



Siliconized CS+

Description

Siliconized CS+ is a high-quality single component modified acrylic joint sealant.

Properties

- Maximum gap filling capacity 6mm.
- Colorfast and waterproof after curing.
- Can be painted with water-based systems.
- Very good adhesion on porous surfaces, aluminum and wood.

Applications

- Joints with movements upto 12.5%
- Connection joints in the building industry
- Joints in windowsills, between skirting-board and floor, between brickwork, etc.

Technical data

Base	Acrylic Dispersion	
Consistency	Paste	
Curing system	Physical Drying	
Specific Gravity (g/ml)	1.67 ± 0.05	
Skin formation (minutes)	Approx. 20	
Shrinkage (%)	DIN 52451	Approx. 15
Maximum allowed Distortion (%)	± 12.5	
Temperature Resistance (°C)	-20 to +80	
Application Temperature (°C)	+5 to +30	

Footnote: Skinning time and curing speed may vary depending on environmental factors such as temperature, moisture, and type of substrates.

Substrates

- Substrate condition
The surface must be rigid, clean, dry, free of dust and grease.
- Substrate preparation
Highly porous surfaces should be primed with diluted Siliconized CS+ (1 part Siliconized CS+ and 2 parts water).
- Substrate types
Siliconized CS+ has good adhesion to all common porous building substrates.
Siliconized CS+ has no good adhesion or is not suitable for PE, PP, PTFE (Teflon®), bituminous substrates, copper or copper containing materials such as bronze and brass.

We recommend a preliminary adhesion test on every surface.





Siliconized CS+

Application method

- Application method
Apply the product with a manual, pneumatic or a battery-operated caulking gun.
- Cleaning method
Before curing, Siliconized CS+ can be removed with water from substrates and tools. Cured sealant must be removed mechanically.
- Finishing method
Finish with a spatula or putty knife.
- Repair method
Repair with the same material.

Joint Size

Minimum Width: 5 mm
Maximum Width: 20 mm
Minimum Depth: 5 mm
Recommendation for sealing jobs: Joint Depth = Joint Width

Use PE backer rods in case of large joint dimensions to avoid three-point adhesion.

Health and Safety Recommendations

Take the usual labour hygiene into account. Consult the packaging label and safety data sheet for more information.
Dangerous. Respect the precautions for use.

Packaging/Logistics

Colour: White
Packaging: 450g Cartridge
Shelf life: 12 months from the date of production. The product must be stored in its original, undamaged, and sealed packaging under dry conditions, protected from direct sunlight, and at temperatures between +5°C and +25°C.

Remarks

- Do not use in applications where continuous water immersion is possible.
- Paintable with most paints, However given the great diversity in available paints, it is recommended to do a compatibility test prior to the application.
- Do not apply when rain or frost is imminent.
- The paint should be sufficiently elastic to be applied on a plasto-elastic sealant. A preliminary test is recommended to prevent cracking.
- Not suitable for glass & mirrors.

This technical data sheet supersedes all earlier versions. The information provided is based on our tests and practical experience and is supplied in good faith as general guidance only, without creating any liability. Since materials, substrates, application design, and processing conditions vary widely and are outside our control, we cannot accept responsibility for the results obtained from use of this information. The user must verify suitability for the intended application through their own testing, and preliminary trials are recommended in all cases. The manufacturer reserves the right to change product specifications without prior notice.